






MOLYDUVAL

Carat 11



Biodegradable Lubrication Paste

MOLYDUVAL Carat 11 is a light colour, PTFE containing multipurpose lubricant grease for lubrication points with extreme pressures and high temperatures.

MOLYDUVAL Carat 11 is based on biodegradable base fluids.

Characteristics

- prevents fretting corrosion
- reduces wear
- prevents stick-slip
- good tackiness
- best corrosion protection
- biodegradable

Applications

- for lubrication of open gears
- for lubrication of oscillating machine parts, f.e. clamping chucks
- for lubrication of sliding surfaces, where a dark or black lubrication paste is not desired because of contamination, f.e. at textile-, paper- or packing machinery or in precision engineering, food industry
- for lubrication of plastic seals and rubber
- for assembly of connections of any kind

How To Use

Apply thin and even with brush or rag on the cleaned surfaces. Lubricate frequently at high temperatures if possible.

TECHNICAL DATAS	Specifications	Unit	
Name	DIN 51502		MEPF1.5E-02
Base oil			Natural Esters
Color			White
Density at 15°C	SEB 181301	kg/m³	1200
Penetration worked	DIN ISO 2137	0,1·mm	290-310
Penetration unworked	DIN ISO 2137	0,1·mm	290-310
Consistency Class NLGI	DIN 51818		1-2
Temperature range		°C	-20 up to 120
Water resistance	DIN 51807	grade	0-90

For more information call +49 2102 9757-28 or contact us at <http://www.molyduval.com> αβχδε

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.