




MOLYDUVAL

Carat 26



White Lubrication Paste

MOLYDUVAL Carat 26 is a light colour solid lubricant containing multipurpose lubrication paste, which forms a thin, very pressure stable and solid lubricant containing I film, preventing stick - slip and fretting corrosion.

MOLYDUVAL Carat 26 is the on of our best lubricants in case of oscillation or vibration.

Characteristics

- prevents fretting corrosion
- reduces wear
- prevents stick-slip
- absolutely water refusing
- good tackiness
- best corrosion protection
- non-toxic

Applications

- for assembly of connections of any kind
- for lubrication of oscillating machine parts, f.e. clamping chucks
- for lubrication of sliding surfaces, where a dark or black lubrication paste is not desired because of contamination, f.e. at textile-, paper- or packing machinery or in precision engineering
- for cold forming of metals

How To Use

Apply MOLYDUVAL Carat 26 thin and even with brush or rag on the cleaned surfaces. Lubricate frequently at high temperatures if possible.

TECHNICAL DATAS	Specifications	Unit	
Name	DIN 51502		MLPF2-30
Base oil			Mineral Oil
Color			white, cream
Density at 15°C	SEB 181301	kg/m³	1150
Penetration worked	DIN ISO 2137	0,1·mm	250-270
Penetration unworked	DIN ISO 2137	0,1·mm	265-295
Consistency Class NLGI	DIN 51818		2
Temperature range		°C	-30 up to 150

For more information call +49 2102 9757-28 or contact us at <http://www.molyduval.com> αβχδε

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.